



Illinois Wesleyan University Digital Commons @ IWU

John Wesley Powell Student Research
Conference

2004, 15th Annual JWP Conference

Apr 17th, 9:00 AM - 10:00 AM

Adaptive Optics for Dynamic Optical Traps

Olukayode Karunwi

Illinois Wesleyan University

Ryan Smith

Illinois Wesleyan University

Gabriel Spalding, Faculty Advisor

Illinois Wesleyan University

Follow this and additional works at: <http://digitalcommons.iwu.edu/jwprc>

Olukayode Karunwi; Ryan Smith; and Gabriel Spalding, Faculty Advisor, "Adaptive Optics for Dynamic Optical Traps" (April 17, 2004). *John Wesley Powell Student Research Conference*. Paper 16.
<http://digitalcommons.iwu.edu/jwprc/2004/posters/16>

This Event is brought to you for free and open access by The Ames Library, the Andrew W. Mellon Center for Curricular and Faculty Development, the Office of the Provost and the Office of the President. It has been accepted for inclusion in Digital Commons @ IWU by the faculty at Illinois Wesleyan University. For more information, please contact digitalcommons@iwu.edu.

©Copyright is owned by the author of this document.

Poster Presentation P25

ADAPTIVE OPTICS FOR DYNAMIC OPTICAL TRAPS

Olukayode Karunwi, Ryan Smith and Gabriel Spalding*
Department of Physics, Illinois Wesleyan University

Holographic Optical Tweezers were first demonstrated by Fournier, *et al*¹, using a commercial hologram. A complete recipe for making *tailored*, planar arrays of optical traps using Diffractive Optical Elements (DOE) was laid out in the IWU – Univ. of Chicago collaboration, “Computer-Generated Holographic Optical Tweezer Arrays.”² While this original “HOT” recipe dealt with two-dimensional arrays, several generalizations have been demonstrated which extend the basic method to three-dimensions^{3, 4}. That said, three-dimensional studies remain in their infancy. Furthermore, even for lower-dimensional arrays, both errors in the DOE and aberrations in the optical system can compromise trap performance. We will report on our progress in using a Programmable Phase Modulator (an optically addressable DOE) to provide a reconfigurable, self-calibrating DOE, and to correct for aberrations. Our approach involves modifying the “HOT” algorithm in order to provide a feedback mechanism between the input optical array and output optical array.

- ¹ J.-M. R. Fournier, M. M. Burns, and J. A. Golovchenko, Proceedings SPIE — The International Society for Optical Engineering **2406**, 101 (1995).
- ² E. R. Dufresne, G. C. Spalding, M. T. Dearing, et al., Review of Scientific Instruments **72**, 1810 (2001).
- ³ H. Melville, G. F. Milne, G. C. Spalding, et al., Optics Express (2003).
- ⁴ J. Leach, G. Sinclair, P. Jordan, et al., Optics Express **12**, 220 (2004).